

tesa Powerbond® Outdoor – 55750/ 55751

Strong double sided and self-adhesive tape with acrylic adhesive mass.

Main Application

tesa Powerbond® Outdoor is suitable for long-lasting, secure and fast interior- and exterior mounting of multiple objects on solid surfaces.

- Holds on tiles, steel, most metals, glass, painted wood and plastics: PMMA (Acryl glass), PS, H-PVC, PET, PC and ABS
- Recommendation for application: flat objects up to 10mm thick with 10cm tape per kg. For objects weighing no more than 2kg.

For optimal results:

Preparation: Clean the surfaces with rubbing alcohol and work on/ with flat, dry, dust and grease-free surfaces.

Application: Apply vertically as shown on the packaging, overhead mounting is not recommended. Apply the adhesive tape to the rougher surface first. Press down firmly and evenly on the entire tape for at least five seconds to secure the bond. The total weight per meter is not meant to be applied in one piece. The declared holding power is based on the parameters: flat object with a max. depth of 10mm.

Please note:

- Do not touch the adhesive area of the tape.
- Not suitable for use on vinyl wallpaper and anti-stick surfaces.
- Glass cleaners for preparing the surface could reduce the holding power (contains e.g. silicones: Silicone prevents an adhesive bonding and cannot be removed from surfaces with cleaners).


Technical Data & Properties

Dimensions	55750: 1,5m x 19mm; 55751: 5m x 19mm
Product Structure	3 layer
Colour	Translucent
Thickness without liner	1,14 mm
Liner	Double-sided siliconised foil
Adhesive	Acrylic adhesive mass
Storage Time	12 months
Application Temperature	Min. 15°C
Temperature Resistance	15 – 80°C
UV Resistance	Yes
Humidity Resistance	Yes
Holding Power	1 kg/10 cm (lever ≤ 10mm)

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Pictures



55750



55751

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.